

## Dew Point Mirror 473



### Reliable Measurement

The Model 473 Dew Point Mirror is a portable instrument equipped with a separate measuring head for both spot and continuous measurement of Dew/Frost point and temperature in air and gas mixtures. Based on the chilled mirror principle, the 473 ensures direct and accurate humidity measurement.

### Full Color Touch Screen

The system uses a full color active matrix liquid crystal display with an integral touch panel. It has a high contrast ratio and a wide viewing angle for easy readability. Data is displayed in large easy to read fonts. Using the on screen buttons and menus, you can easily configure each line of the display for a variety of humidity, temperature, and pressure parameters that may be viewed in either SI or non-SI units. A simple touch of a button toggles any parameter between numeric or graph format.

### Remote Measuring Head

The measuring head is separate from the control/display unit for use in chambers and other environments of various humidity/temperature ranges without the need for external heating of the gas path. A mounting kit for pipes and tubes, including flowmeter and valve, is available as an option. For measurement of environment temperature, a separate temperature sensor is either mounted on the measuring head or available as a separate remote probe with a connection to the instrument back panel.

### Analog & Digital I/O

The 473 is equipped with an RS-232 digital output and optionally with two user-scalable analog outputs for recording or remote readout of the measured and calculated values.

### Verifiable Calibration

Easily check the calibration at any time using the built-in Ice Test function, providing instant verification of system integrity.

<b>Model:</b>	<b>473</b>
---------------	------------

Measuring range:	
Frost/Dew Point	-20...+70°C
% RH	5...100%
Temperature	-20...+80°C
Accuracy:	
Frost/Dew point	±0.2°C
Temperature	±0.1°C
Reproducibility:	
Frost/Dew Point	± 0.1°C
Temperature	± 0.05°C
Thermoelectric Mirror cooling:	2-stage, 50°C depression
Cooling:	Air
Display:	Active Matrix Color Graphic LCD
Digital I/O:	RS-232
Mirror temperature sensor:	PRT-100
Operation temperature:	
Instrument	-10...+40°C
Measuring head	-20...+80°C
Storage temperature:	-10...+50°C
Ambient humidity Instrument:	90% RH max., non condensing
Voltage:	100...240 VAC, 50/60 Hz (Battery operation optional)
Power consumption:	100 Watt
Width:	265 mm
Height:	155 mm
Depth:	265 mm
Weight:	5 kg

We reserve the right to change design or technical data without notice.

MBW Calibration Ltd.  
Seminarstrasse 57  
CH-5430 Wettingen  
Switzerland

Phone +41 56 426 21 33  
Fax +41 56 427 14 00

info@mbw.ch  
www.mbw.ch